



## Graduate USB (USD10)



### Specifications:

The 'Alumni Graduate' USB, the new look in the aluminum enclosures series for 2.5" hard drives. Slim, compact and versatile, this unit fits in every pocket. Optional power adapter available for non bus powered hosts or PCMCIA cards.

**Model No.:** GA-USB

**Bridge Chipset:** AU6390

**Case Material:** Aluminum

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 9.5mm)

### Interface/Ports:

USB 2.0 (USB1.1) 1 port (mini 5pin)

### Data Transfer:

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

Bus Power (USB only) USB power cable

Optional External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.6A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 12.5cm x 7.8cm x 1.8cm

### Packing Accessories:

Graduate USB Enclosure

USB 2.0 cable (5pin x 4pin)

Manual, carrying case, screw package, screw driver, USB power cable, driver CD

**Remarks:** \* Enclosure made for parallel ATA hard drive



## Graduate SATA (USD15.5)



### Specifications:

The 'Alumni Graduate' SATA, the new look in the aluminum enclosures series for 2.5" hard drives\*. Slim, compact and versatile, this unit fits in every pocket. Optional power adapter available for non bus powered hosts or PCMCIA cards.

**Model No.:** GA-SATA

**Bridge Chipset:** J-Micron 20339

**Case Material:** Aluminum

**Application:** Any 2.5" Serial ATA Hard Drive (Notebook size HDD up to 9.5mm)

**Interface/Ports:** USB 2.0 (USB1.1) 1 port (mini 5pin)

### Data Transfer:

Serial ATA up to 1.5Gbps (150MB/sec)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

Bus Power (USB only) USB power cable

Optional External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.6A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 12.5cm x 7.8cm x 1.8cm

### Packing Accessories:

Graduate s2 Enclosure

USB 2.0 cable (5pin x 4pin)

Serial ATA cable (7pin x 7pin)

Manual, carrying case, screw package, screw driver, USB power cable, driver CD

**Remarks:** \* Serial ATA not supported on Mac OS



## Graduate 400+ (USD27.5)



### Specifications

The 'Alumni Graduate' 400+ (1394a/USB2.0), the new look in the aluminum enclosures series for 2.5" hard drives. Slim, compact and versatile, this unit fits in every pocket. Optional power adapter available for non bus powered hosts or PCMCIA cards.

**Model No.:** GA- 400+

**Bridge Chipset:** PL-3507C

**Case Material:** Aluminum

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 9.5mm)

### Interface/Ports:

FireWire 400 (1394a) 1 port (6pin)

USB 2.0 (USB1.1) 1 port (mini 5pin)

### Data Transfer:

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

FireWire 400 (1394a): Windows 98SE/ME/2000/XP

(The first version of Windows 98 does not support 1394a)

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

FireWire 400 (1394a): Mac OS 9.1 or higher

(You must update the firewire extension to v2.6 or higher between Mac OS 8.6 and Mac OS 9.04)

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

Bus Power (when Host provides power)

USB power cable

Optional External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.6A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 12.5cm x 7.8cm x 1.8cm

### Packing Accessories:

Graduate 400+ Enclosure

USB 2.0 cable (5pin x 4pin)

Firewire 1394a cable (6pin x6pin)



Manual, carrying case, screw package, screw driver, USB power cable, driver CD

**Remarks:** Prolific chipset PL-3507 available

## PD2500-USB (USD12.5)



### Specifications:

The PD2500-USB, the new look in the aluminum enclosures series for 2.5" hard drives. Slim, compact and versatile, this unit fits in every pocket. Optional power adapter available for non bus powered hosts or PCMCIA cards. Features fan less design and passive cooling, ideal for offices and quiet working environments.

**Model No.:** PD2500-USB

**Bridge Chipset:** Cypress 68300B

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 9.5mm)

### Interface/Ports:

USB 2.0 (USB1.1) 1 port (mini 5pin)

### Data Transfer:

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

Bus Power (USB only) USB power cable

Optional External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.6A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 12.5cm x 7.8cm x 2.0cm

### Packing Accessories:

PD2500-USB Enclosure

USB 2.0 cable (5pin x 4pin)

Manual, carrying case, screw package, screw driver, USB power cable, driver CD



## PD2500-SATA (USD17.5)



### Specifications:

The PD2500-SATA, the new look in the aluminum enclosures series for 2.5" Serial ATA hard drives. Slim, compact and versatile, this unit fits in every pocket. Optional power adapter available for non bus powered hosts or PCMCIA cards. Features fan less design and passive cooling, ideal for offices and quiet working environments.

**Model No.:** PD2500-SATA

**Bridge Chipset:** J-Micron 20339

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Any 2.5" Serial ATA Hard Drive (Notebook size HDD up to 9.5mm)

**Interface/Ports:** USB 2.0 (USB1.1) 1 port (mini 5pin)

### Data Transfer:

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

Serial ATA: Windows 2000/XP

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

Bus Power (USB only) USB power cable

Optional External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.6A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 12.5cm x 7.8cm x 2.0cm

### Packing Accessories:

PD2500-SATA Enclosure

USB 2.0 cable (5pin x 4pin)

Serial ATA cable (7pin x 7pin)

Manual, carrying case, screw package, screw driver, USB power cable, driver CD



## PD2500-400+ (USD30)



### Specifications:

The PD2500-SATA, the new look in the aluminum enclosures series for 2.5" hard drives. Slim, compact and versatile, this unit fits in every pocket. Optional power adapter available for non bus powered hosts or PCMCIA cards. Features fan less design and passive cooling, ideal for offices and quiet working environments.

**Model No.:** PD2500- 400+

**Bridge Chipset:** PL-3507C

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 9.5mm)

### Interface/Ports:

FireWire 400 (1394a) 1 port (6pin)

USB 2.0 (USB1.1) 1 port (mini 5pin)

### Data Transfer:

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

FireWire 400 (1394a): Windows 98SE/ME/2000/XP

(The first version of Windows 98 does not support 1394a)

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

FireWire 400 (1394a): Mac OS 9.1 or higher

(You must update the firewire extension to v2.6 or higher between Mac OS 8.6 and Mac OS 9.04)

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

Bus Power (when Host provides power)

USB power cable

Optional External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.6A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 12.5cm x 7.8cm x 1.8cm

### Packing Accessories:



Graduate 400+ Enclosure

USB 2.0 cable (5pin x 4pin)

Firewire 1394a cable (6pin x6pin)

Manual, carrying case, screw package, screw driver, USB power cable, driver CD

**Remarks:** Prolific chipset PL-3507 available

## Clearlight USB 2.0 (USD18.5)



### Specifications:

The 'Clearlight' USB 2.0 is a slim, compact, outstanding looking polycarbonate enclosure made for all types of 2.5" hard drives. Good handling and high performance makes accessing your data even easier and more efficient.

**Model No. :** CL-USB

**Bridge Chipset:** Cypress 68300B

**Case Material:** PC plastic

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 12.5mm)

**Interface/Ports:** USB 2.0 (USB1.1) 1 port (4pin)

### Data Transfer:

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.4A, 50-60Hz Output: DC +5V/2A

**Enclosure Size:** 14.0cm x 8.8cm x 2.6cm

### Packing Accessories:

Clearlight USB 2.0 Enclosure

USB 2.0 cable (4pin x 4pin)

Manual, power adapter, screw package, hook, driver CD

**Remarks:** Transparent enclosure available on request



## Clearlight 400 (USD33)



### Specifications:

The 'Clearlight' FireWire 1394a is a slim, compact, outstanding looking polycarbonate enclosure made for all types of 2.5" hard drives. Good handling and high performance makes accessing your data even easier and more efficient.

**Model No. :** CL-400

**Bridge Chipset:** Oxford 911+

**Case Material:** PC plastic

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 12.5mm)

**Interface/Ports:** FireWire 400 (1394a) 2 port (6pin)

**Data Transfer:** FireWire 400 (1394a) up to 400Mbps (50MB/s)

### Windows Requirements:

FireWire 1394a: Windows 98SE/ME/2000/XP

(The first version of Windows 98 does not support 1394a)

Your hardware device must have proper port or PCI card

### Mac Requirements:

FireWire 1394a: Mac OS 9.1 or higher

(You must update the firewire extension to v2.6 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

Bus Power (when Host provides power)

Optional External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.4A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 14.0cm x 8.8cm x 2.6cm

### Packing Accessories:

Clearlight 400 Firewire Enclosure

Firewire 1394a cable (6pin x 6pin)

Manual, screw package, hook

**Remarks:** Silver version available on request

## Clearlight 400+ (USD38.9)



### Specifications:

The 'Clearlight' 400+ (1394a/USB2.0) is a slim, compact, outstanding looking polycarbonate enclosure made for all types of 2.5" hard drives. Good handling and high performance makes accessing your data even easier and more efficient.





**Model No. :** CL-400+

**Bridge Chipset:** Cypress 68300B /Oxford 911+

**Case Material:** PC plastic

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 12.5mm)

**Interface/Ports:**

FireWire 400 (1394a) 1 port (6pin), 1port (4pin)

USB 2.0 (USB1.1) 1 port (4pin)

**Data Transfer:**

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

**Windows Requirements:**

FireWire 400 (1394a): Windows 98SE/ME/2000/XP

(The first version of Windows 98 does not support 1394a)

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

**Mac Requirements:**

FireWire 400 (1394a): Mac OS 9.1 or higher

(You must update the firewire extension to v2.6 or higher between Mac OS 8.6 and Mac OS 9.04)

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

**Power Supply:**

External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.4A, 50-60Hz

Output: DC +5V/2A

**Enclosure Size:** 14.0cm x 8.8cm x 2.6cm

**Packing Accessories:**

Clearlight 400+ Enclosure

USB 2.0 cable (4pin x 4pin)

Firewire 1394a cable (6pin x6pin)

Manual, power adapter, screw package, hook, driver CD

**Remarks:** Transparent version available on request

## K3-USB (USD27.5)





**Model No. : K3-USB**

**Bridge Chipset:** Cypress 68300B

**Case Material:** Quality aluminum colored plastic

**Application:** Single 3.5" IDE HDD (ATA-6 compatible)

**Interface/Ports:** USB 2.0 High Speed (USB1.1 compatible) 1 port

**Data Transfer:**

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

**System Requirements (PC) :**

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

**System Requirements (Mac) :**

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

**Power Supply:**

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/3A

**Enclosure Size:** 21.2cm x 12.85cm x 4cm

**Packing Accessories:**

K3 Enclosure

USB 2.0 cable (4pin x 4pin)

Power adapter plus cord, screw package, driver CD, manual

## K3-SATA (USD29.5)



**Model No. : K3-SATA**

**Bridge Chipset:** Sunplus 215A

**Case Material:** Quality aluminum colored plastic

**Application:** Single 3.5" **SATA** HDD (SATA-I up to 3Gb)

**Interface/Ports:** USB 2.0 High Speed (USB1.1 compatible) 1 port

**Data Transfer:**

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)



## System Requirements (PC) :

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

## System Requirements (Mac) :

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

## Power Supply:

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/3A

**Enclosure Size:** 21.2cm x12.85cm x 4cm

## Packing Accessories:

K3 Enclosure

USB 2.0 cable (4pin x 4pin)

Power adapter plus cord, screw package, driver CD, manual

## K3-eSATA (USD38.5)



**Model No. :** K3-eSATA

**Bridge Chipset :** J-micro 20336

**Case Material:** High quality aluminum colored plastic

**Application:** Single 3.5" SATA-II Hard Drive (3Gb/s)

**Interface/Ports:** USB 2.0 High Speed (USB1.1 compatible) 1 port and eSATA 1port eSATA

## Data Transfer:

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

eSATA up to 3.0Gbps (300MB/s)

## System Requirements (PC) :

eSATA: Windows 2000/XP

USB 2.0: Windows ME/2000/XP

USB 1.1: Windows ME/2000/XP

Your hardware device must have proper port or PCI card. eSATA 1.5Gbps Plug and Play support required for host card driver.



## System Requirements (Mac) :

eSATA: Mac OS 10.2 or higher

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card. eSATA 1.5Gbps Plug and Play support required for host card driver.

## Power Supply:

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/3A

**Enclosure Size:** 21.2cm x12.85cm x 4cm

## Packing Accessories:

K3-eSATA Enclosure

eSATA cable

USB 2.0 cable (5 to 4pin)

Power adapter plus cord, screw package, manual

**Remarks:** J-Micron 20336 is applicable Serial ATA hard disk, the output Interface is the esata+USB2.0

## Pleiades USB 2.0 (USD30)



## Specifications:

The next generation Ice Cube 'Pleiades USB 2.0', a slim, stylish and powerful aluminum enclosure for your 3.5" hard drive. Features fan less design and passive cooling, ideal for multi-media users and quiet working environments.

**Model No. :** PD-USB

**Bridge Chipset:** Cypress 68300B

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" IDE HDD (ATA-6 compatible)

**Interface/Ports:** USB 2.0 High Speed (USB1.1 compatible) 1 port

## Data Transfer:

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

## System Requirements (PC) :

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)



## System Requirements (Mac) :

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

## Power Supply:

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

## Packing Accessories:

Pleiades USB 2.0 Enclosure

USB 2.0 cable (4pin x 4pin)

Power adapter plus cord, feet, screw package, driver CD, manual

## Pleiades-SATA (USD34.5)



## Specifications:

The 'Pleiades USB-FX', a slim, stylish and powerful aluminum enclosure for your 3.5" Serial or Parallel ATA hard drive. Features fan less design and passive cooling, ideal for multi-media users and quiet working environments.

**Model No. :** PD-SATA

**Bridge Chipset:** J-Micron 20337

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" IDE or SATA HDD (SATA-I up to 1.5Gb)

**Interface/Ports:** USB 2.0 High Speed (USB1.1 compatible) 1 port

**Data Transfer:** USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

## System Requirements (PC) :

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

## System Requirements (Mac) :

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

## Power Supply:

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)



Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +5V/2A, +12V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

**Packing Accessories:**

Pleiades USB 2.0 Enclosure

USB 2.0 cable (4pin x 4pin)

Power adapter plus cord, feet, screw package, driver CD, manual

**Remarks** \* only one hard drive can be installed, either a SATA or IDE hard drive.

**Pleiades-eSATA (USD49.5)**



**Specifications:**

The 'Pleiades S2' is designed for your 3.5" Serial ATA hard drive, featuring fanless design and passive cooling. Available with both USB 2.0 High Speed and eSATA connection options, the Pleiades S2 is a sleek, high-performance enclosure designed for the modern home/office environment.

**Model No. :** PD-eSATA

**Bridge Chipset:** J-Micron 20336

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" SATA-I or SATA-II Hard Drive (1.5Gb/s or 3.0Gb/s)

**Interface/Ports:**

eSATA 1port

USB 2.0 High Speed (USB 1.1 compatible) 1 port

**Data Transfer:**

eSATA up to 3.0Gbps (300MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

**System Requirements (PC) :**

eSATA: Windows 2000/XP

USB 2.0: Windows ME/2000/XP

USB 1.1: Windows ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card). eSATA Plug and Play support required for host card driver.

**System Requirements (Mac) :**

eSATA: Mac OS 10.2 or higher

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card). eSATA Plug and Play support required for host card driver.

**Power Supply:**



External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

**Packing Accessories:**

Pleiades Super S2 Enclosure

eSATA cable

USB 2.0 High Speed cable

Power adapter plus cord, manual

**Pleiades 400 (USD35.7)**



**Specifications:**

The next generation IceCube 'Pleiades 400' (Firewire 1394a), a slim, stylish and powerful aluminum enclosure for your 3.5" hard drive. Features fan less design and passive cooling, ideal for multi-media users and quiet working environments.

**Model No. :** PD-400

**Bridge Chipset:** Oxford 911+

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" IDE HDD (ATA-6 compatible)

**Interface/Ports:** FireWire 400 (1394a) 2 ports

**Data Transfer:** FireWire 400 (1394a) up to 400Mbps (50MB/s)

**System Requirements (PC) :**

FireWire 1394a: Windows 98SE/ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

**System Requirements (Mac) :**

FireWire 1394a: Mac OS 9.1 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

**Power Supply:**

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

**Packing Accessories:**

Pleiades 400 Firewire Enclosure

Firewire 1394a cable (6pin x 6pin)

Power adapter plus cord, stand, screw package, manual



## Pleiades 400+ (USD45.6)



### Specifications:

The next generation IceCube 'Pleiades' 400+ (1394a&USB2.0), a slim, stylish and powerful aluminum enclosure for your 3.5" hard drive. Features fan less design and passive cooling, ideal for multi-media users and quiet working environments.

**Model No. :** PD-400+

**Bridge Chipset:** Oxford 911+/Cypress 68300B

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" IDE HDD (ATA-6 compatible)

### Interface/Ports:

FireWire 400 (1394a) 2 ports

USB 2.0 High Speed (USB1.1 compatible) 1 port

### Data Transfer:

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### System Requirements (PC) :

FireWire 400 (1394a): Windows 98SE/ME/2000/XP

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

### System Requirements (Mac) :

FireWire 400 (1394a): Mac OS 9.1 or higher

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

### Power Supply:

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.7cm x 13.7m x 3.5cm

### Packing Accessories:

Pleiades 400+ Enclosure

USB 2.0 cable (4pin x 4pin)

Firewire 1394a cable (6pin x6pin)

Power adapter plus cord, feet, screw package, driver CD, manual





## Pleiades 800+ (USD60.8)



### Specifications

The next generation IceCube 'Pleiades 800+' (Firewire 800 & USB 2.0), a slim, stylish and powerful aluminum enclosure for your 3.5" hard drive. Features fan less design and passive cooling, ideal for multi-media users and quiet working environments.

**Model No. :** PD-800+

**Bridge Chipset:** Oxford 912/Prolific 2507C

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" IDE HDD (ATA-6 compatible)

### Interface/Ports:

FireWire 800 (1394b) 2 ports

FireWire 400 (1394a) 1 port

USB 2.0 High Speed (USB1.1) 1 port

### Data Transfer:

Firewire 800 (1394b) up to 800Mbps (100MB/s)

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### System Requirements (PC) :

FireWire 800 (1394b): Windows 2000/XP

FireWire 400 (1394a): Windows 98SE/ME/2000/XP

USB 2.0: Windows ME/2000/XP

USB 1.1: Windows ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

### System Requirements (Mac) :

FireWire 800 (1394b): Mac OS 10.2 or higher

FireWire 400 (1394a): Mac OS 9.1 or higher

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card)

### Power Supply:

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

### Packing Accessories:



Pleiades 800+ Enclosure

USB 2.0 cable (5pin x 4pin)

Firewire 1394b cable (9pin x9pin)

Power adapter plus cord, feet, screw package, manual

## Pleiades S800+ (USD63.8)



### Specifications

The 'Pleiades Super S-Combo' (Firewire 400/800, USB 2.0, eSATA) is as of today, the most powerful and versatile aluminum enclosure for your 3.5" SATA hard drive. Features fan less design and passive cooling, ideal for multi-media users and quiet working environments.

**Model No. :** PD-S800+

**Bridge Chipset:** Oxford 924 DSB

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" SATA-I or SATA-II Hard Drive (1.5Gb/s)

### Interface/Ports:

eSATA 1port

FireWire 800 (1394b) 2 ports

FireWire 400 (1394a) 1 port

USB 2.0 High Speed (USB 1.1 compatible) 1 port

### Data Transfer:

eSATA up to 1.5Gbps (150MB/s)

Firewire 800 (1394b) up to 800Mbps (100MB/s)

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### System Requirements (PC) :

eSATA: Windows 2000/XP

FireWire 800 (1394b): Windows 2000/XP

FireWire 400 (1394a): Windows ME/2000/XP

USB 2.0: Windows ME/2000/XP

USB 1.1: Windows ME/2000/XP

Your hardware device must have proper port or PCI card. eSATA 1.5Gbps Plug and Play support required for host card driver.

### System Requirements (Mac) :

eSATA: Mac OS 10.2 or higher



FireWire 800 (1394b): Mac OS 10.2 or higher

FireWire 400 (1394a): Mac OS 9.1 or higher

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card. eSATA 1.5Gbps Plug and Play support required for host card driver.

#### **Power Supply:**

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

#### **Packing Accessories:**

Pleiades Super S-Combo Enclosure

eSATA cable

USB 2.0 cable (5 to 4pin)

Firewire 1394a cable (6 to 6pin)

Firewire 1394b cable (9 to 9pin)

Power adapter plus cord, feet, screw package, manual

## **Pleiades USB/LAN (USD46)**



#### **Specifications:**

The latest member of the 'Pleiades' family now offers both USB 2.0 High Speed and LAN in one unit! A slim, stylish and powerful aluminum enclosure for your 3.5" hard drive, designed to share and access your data, no matter where you are. Features fan less design and passive cooling, ideal for offices and quiet working environments.

**Model No. :** PD-LNU2RGS

**Bridge Chipset:** GL-811E 811 & LAN(RDC2882)

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" parallel ATA hard drive 20-500GB FAT32

#### **Interface/Ports:**

10/100Base-TX Auto MDI/MDI-X, 1 port (RJ-45)

USB 2.0 High Speed (USB1.1), 1 port (4pin)

**LAN Speed:** Half-Duplex and Full-Duplex operation



**Protocol:** TCP/IP

**Network File System:** CIFS(SMB), FTP

**Maximum Sessions:** Up to 8 simultaneous connections

**Web Based Configuration Network:** DHCP Server, DHCP Client, Auto IP, Fixed IP

**FTP Server:** Setup for Accounts, Status, Access Right

**Samba Server:** Share Level Access, NBNS Support

**System Tools:** Standard Settings, Formatting, SNTP, Firmware Upgrade

**Environment Operating Temperature:** 5°C ~ 40°C

**Operating Humidity:** 10%RH ~ 80%

**Storage Temperature:** -20°C ~ 70°C

**Storage Humidity:** 5%RH ~ 90%RH

**System Requirements (PC) :**

LAN: Windows 98SE/ME/2000/XP

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

**System Requirements (Mac) :**

LAN: Mac OS X (Samba/FTP)

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card

**Power Supply:**

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

**Packing Accessories:**

Pleiades USB/LAN Enclosure

USB 2.0 cable (4pin x 4pin)

Ethernet cable

Power adapter plus cord, feet, screw package, driver CD, manual

## Pleiades NDAS (USD80)



**Specifications:**

The 'Pleiades NDAS' features NDAS technology, delivering high performance for sharing your disk on the local network yet keeping it as simple as a standard Plug and Play device. On top of that, it also supports the flexible and familiar USB 2.0 High Speed interfaces all in one unit! Extending your storage space has not only just become a lot easier but faster too at the same time.

**Model No. :** PD-LINUXPS

**Bridge Chipset:** Ximeta NDAS 2011 & Prolific 2507C

**Case Material:** Aluminum with internal metal chassis for optimized heat dissipation

**Application:** Single 3.5" parallel ATA hard drive , 20-500GB , FAT32/NTFS/HFS+

**Interface/Ports:**

100Base-TX Auto MDI/MDI-X, 1 port (RJ-45)

USB 2.0 High Speed (USB1.1), 1 port (4pin)

**LAN Speed:** Up to 10MB/s

**Connection:** Proprietary Driver Solution

**Maximum Sessions:** Up to 20 simultaneous connections

**Driver Based Configuration Menu Languages:**

English, German, Spanish, French, Italian, Portuguese, Japanese, Korean

**Access Management and Options:**

Mount & Unmount, Activation, Registration, Write Key, Read Only, Suspend & Hibernation Support

**Device Info:**

Drive Status, Device Properties, Hardware Details, Mac & IP Address, Connection & Confirmation Alerts

**Environment Operating Temperature:** 5°C ~ 40°C

**Operating Humidity:** 10%RH ~ 80%

**Storage Temperature:** -20°C ~ 70°C

**Storage Humidity:** 5%RH ~ 90%RH

**System Requirements (PC) :**

LAN: Windows 98SE/ME/2000/XP

USB 2.0: Windows ME/2000/XP

USB 1.1: Windows ME/2000/XP

Your hardware device must have proper port or PCI card

**System Requirements (Mac) :**

LAN: Mac OS 10.3 or higher (Intel based machines not supported)

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card

**Power Supply:**

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +12V/2A, +5V/2A

**Enclosure Size:** 22.8cm x 13.7m x 3.5cm

**Packing Accessories:**

Pleiades NDAS Enclosure

USB 2.0 cable (4pin x 4pin)

Ethernet cable RJ-45

Power adapter plus cord, feet, screw package, driver CD, manual

**Remarks:**



\* Only one interface can be used at the time (either LAN or USB disk)

\*\* FAT32 can be accessed on Mac&PC, NTFS can be accessed on PC but read only on Mac, HFS+ can be accessed on Mac only

\*\*\* Write access for several PC's possible, write access for Mac only one at the time, fewer connections are recommended for best performance

## Pleiades Taurus (USD92.2)



Coming Soon!



### Specifications

When it comes to raw power there is nothing to beat the new dual-bay Pleiades Taurus. Available in the classic Pleiades design, the Taurus is built strong and rugged, offering more than enough capacity to store all your digital media files. Not only that, the Pleiades Taurus can also back up and secure all of your data thanks to RAID protection. Great performance, great protection and great looks – only in the Pleiades Taurus.

**Model No.:** PDD-FBA3U2OS

**Bridge Chipset:** Oxford 924 DSB

**Color:** Silver

**Case Material:** High quality aluminum for optimized heat dissipation

### Application:

Two 3.5" SATA-I or SATA-II Hard Drives (1.5Gb/s)

Identical hard drives recommended (same manufacturer, capacity and RPM)

### Features:

Configurable RAID function for 2 drives (RAID 0 using striping or spanning or Non-RAID)

USB mass-storage compliant (USB 2.0 and USB 1.1)

Supports Firewire 400 and 800 (hardware acceleration for FastStart & small data blocks)

18-Kbyte cache for USB or Firewire data maximizes performance by double-buffering 4-Kbyte packets

SATA II compliant

### Interface/Ports:

FireWire 800 (1394b) 2 ports

FireWire 400 (1394a) 1 port in front

USB 2.0 High Speed (USB 1.1 compatible) 1 port



## Data Transfer:

Firewire 800 (1394b) up to 800Mbps (100MB/s)

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

## System Requirements (PC) :

FireWire 800 (1394b): Windows 2000/XP

FireWire 400 (1394a): Windows ME/2000/XP

USB 2.0: Windows ME/2000/XP

USB 1.1: Windows ME/2000/XP

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card).

## System Requirements (Mac) :

FireWire 800 (1394b): Mac OS 10.2 or higher

FireWire 400 (1394a): Mac OS 9.1 or higher

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.2 or higher

Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card).

## Power Supply:

External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)

Input: AC 100-240V

Output: DC +12V/3A, +5V/4.2A

**Enclosure Size:** 24.5cm x 13.3cm x 7.6cm

## Packing Accessories:

Pleiades Taurus Enclosure

USB 2.0 cable

Firewire 1394a cable (6 to 6pin)

Firewire 1394b cable (9 to 9pin)

Power adapter plus cord, feet, screw package, manual

## M9-DX (USD55)



## Specifications:

The M9-DX is a new Firewire/USB external disk drive enclosure, which also has a built in port replicates. It was created specifically to complement the Mac Mini. Features a specially designed active/passive cooling system.

**Model No. :** M9-FRU2OPS

**Bridge Chipset:** Prolific 2507C / Oxford 911+

**Case Material:** High quality aluminum colored plastic

**Application:** Any single 3.5" Parallel ATA Hard Drive (Desktop size) ATA-6 compatible

**Features:**

- USB 2.0 High-Speed 3-Port Hub
- Firewire 1394a 3-Port Repeater/Hub
- Switch for Firewire or USB hard disk mode
- Smart interactive cooling system with thermal probe automatically regulating fan speed
- Massive passive heat sink to radiate heat away from hard drive
- Smart power switch - M9 will power up and down in tandem with your Mac Mini
- Special micro security slot designed to allow the M9 to be anchored to a desk

**Interface/Ports:**

- FireWire 400 (1394a) 3 ports (6pin)
- USB 2.0 High Speed (USB1.1) 1 port (4pin)
- 1 Port upstream (B Type) / 3 Ports downstream (A Type)

**Data Transfer:**

- FireWire 400 (1394a) up to 400Mbps (50MB/s)
- USB 2.0 up to 480Mbps (60MB/s)
- USB 1.1 up to 12Mbps (1.5MB/s)

**Windows Requirements:**

- FireWire 400 (1394a): Windows 98SE/ME/2000/XP
- USB 2.0: WinME/2000/XP
- USB 1.1: WinME/2000/XP
- Your hardware device must have proper port or PCI card

**Mac Requirements:**

- FireWire 400 (1394a): Mac OS 9.2 or higher
- USB 2.0: Mac OS 10.2 or higher
- USB 1.1: Mac OS 9.2 or higher
- Your hardware device must have proper port or PCI card

**Power Supply:**

- External Power Adapter universal auto-switching (UL, cUL, CE, TUV approved)
- Input: AC 100-240V, 1.2A, 50-60Hz
- Output: DC +5V/1.5A, +12V/1.5A

**Enclosure Size:** 16.51cm x 16.51cm x 3.8 cm

**Packing Accessories:** M9 Enclosure

- USB 2.0 cable (4pin x 4pin)
- Firewire 1394a cable (6pin x6pin)
- Power adapter plus cord, screw package, manual

**Remarks:**

- \*The M9-DX can be used either as Firewire or USB hard disk. Use the switch at the back to change the mode.
- \*\* Seagate Barracuda HDD (160GB and above) can not be mounted. Please consider using a different hard disk.

## K5 USB 2.0 (USD22.9)







## Specifications

The 'K5' USB 2.0 features a fan less design, easy handling plus quick and simple installation, making this an user friendly and high performance storage solution. This external enclosure/casing is made for a single 5.25" DVD-RW/CDRW device.

**Model No.:** K5-U2MA or K5-U2PA (K5-U2CA phased out since June 2004)

**Bridge Chipset:** Prolific 2507C

**Case Material:** ABS plastic

**Application:** Any single 5.25" Parallel ATA CDRW/DVD optical drive

**Interface/Ports:** USB 2.0 (USB1.1) 1 port (4pin)

### Data Transfer:

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

### Windows Requirements:

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

### Mac Requirements:

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

### Power Supply:

External Power Adapter universal auto-switching (UL, TUV, CE)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +5V/2A, +12V/2A

**Enclosure Size:** 25.5cm x 16.5cm x 5.2cm

### Packing Accessories:

K5 USB 2.0 Enclosure

USB 2.0 cable (4pin x 4pin)

Power adapter plus cord, screw package, driver CD

### Remark:

\* Retail Box without color sleeve (white box only)

\*\* DVD drive seen on image for reference only!

## K5 400+ (USD32.8)



## Specifications

The 'K5' 400+ (1394a/USB2.0) features a fan less design, easy handling plus quick and simple installation, making this an user friendly and high performance storage solution. This external enclosure/casing is made for a single 5.25"



DVD-RW/CDRW device.

**Model No.:** K5-FRU2PA

**Bridge Chipset:** Prolific PL-3507C

**Case Material:** ABS plastic

**Application:** Any single 5.25" Parallel ATA CDRW/DVD optical drive

**Interface/Ports:**

FireWire 400 (1394a) 2 port (6pin)

USB 2.0 High Speed (USB1.1) 1 port (4pin)

**Data Transfer:**

FireWire 400 (1394a) up to 400Mbps (50MB/s)

USB 2.0 up to 480Mbps (60MB/s)

USB 1.1 up to 12Mbps (1.5MB/s)

**Windows Requirements:**

FireWire 400 (1394a): Windows 98SE/ME/2000/XP

(The first version of Windows 98 does not support 1394a)

USB 2.0: Windows 98SE/ME/2000/XP

USB 1.1: Windows 98SE/ME/2000/XP

Your hardware device must have proper port or PCI card

**Mac Requirements:**

FireWire 400 (1394a): Mac OS 9.1 or higher

(You must update the firewire extension to v2.6 or higher between Mac OS 8.6 and Mac OS 9.04)

USB 2.0: Mac OS 10.2 or higher

USB 1.1: Mac OS 9.1 or higher

(You must update the USB extension to v1.41 or higher between Mac OS 8.6 and Mac OS 9.04)

Your hardware device must have proper port or PCI card

**Power Supply:**

External Power Adapter universal auto-switching (UL, TUV, CE)

Input: AC 100-240V, 1.2A, 50-60Hz

Output: DC +5V/2A, +12V/2A

**Enclosure Size:** 25.5cm x 16.5cm x 5.2cm

**Packing Accessories:**

K5 400+ Enclosure

USB 2.0 cable (4pin x 4pin)

Firewire 1394a cable (6pin x6pin)

Power adapter plus cord, screw package, driver CD

**Remark:**

\* Retail Box without color sleeve (white box only)

\*\* DVD drive seen on image for reference only!

## MovieStar (USD95)





## Specifications:

'MovieStar' is much more than a portable disk. It allows you to enjoy your favorite movies, music and photos while on the road. It produces HDTV quality Video and Dolby Digital or DTS quality Audio for your pleasure. With lightning-fast USB 2.0, the 'MovieStar' offers hot plug and play, super-speedy data transfer and remarkable versatility. Instant backup! Instant storage! Instant Fun! No more expensive pay per view movies in a lonely hotel.

**Model No.:** MS-U2UGG

**Color:** White

**Case Material:** Transparent high quality polycarbonate plastic

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 12.5mm)

### Playback Media Formats Video:

MPEG-1 (AVI, MPG)

MPEG-2 (AVI, VOB), ISO

MPEG-4 (AVI, DivX, DivX VOD, XviD)

### DivX Subtitle:

SUB (*Micro DVD format*), SRT (*Sub RIP format*), SMI (*SAMI format*), Embedded Multiple Subtitle support

**Audio:** WAV, MP3, MPEG-4 (AAC), WMA, AC3. OGG Vorbis

**Photo:** JPG baseline and progressive up to 8 mega pixel

**Bus Interface** USB 2.0 High Speed (USB1.1 backwards compatible)

### Output Interfaces:

**Video:** NTSC/PAL Composite Video, S-Video, Analog YPbPr Video,

SCART RGB, VGA (1024x768), HDTV (480p, 720p, 1080i)

**Audio:** Dual Stereo Analog Audio supporting compressed Dolby Digital 5.1 and DTS pass through

### System Requirements:

Windows 98SE, Win2000, WinME, WinXP

Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card

### Power Supply:

External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.4A, 50-60Hz      output: DC +5V/2A      Bus Power

**Enclosure Size:** 14.0cm x 8.8cm x 2.6cm

### Packing Contents:

MovieStar

USB 2.0 cable, AV cable, SPDIF Coaxial Cable

Infrared Remote Control

Power Adapter

Manual, screw package, driver CD

### Remarks:

\* ISO = One image file backup of the complete DVD. 'MovieStar' will play the ISO file exactly the same as if it was running from the original DVD!

\*\* [Additional accessories](#) available on request

\*\*\* Official DivX Certified™ product. Plays DivX® 5, DivX® 4, DivX® 3 and DivX® VOD video content (in compliance with DivX Certified™ technical requirements)

\*\*\*\* AAC stands for "[Adaptive Audio Coding](#)" and does not support AAC files created by iTunes!



# Does not support High Definition content (DivX HD/WMV9)

## Mvisto Ligh (USD55)



### Specifications:

Light weight, compact design, and pocket media player with high quality aluminum housing. It allows you to enjoy your favorite movies, music and photos while at home or when traveling. It produces high quality video and audio. With lightning-fast USB 2.0, the 'Mvisto Light' offers hot plug and play, super-speedy data transfer and remarkable versatility. Instant backup! Instant storage! Instant Fun!

**Model No.:** ML-U2EGS

**Color:** Silver

**Case Material:** High Quality Aluminum

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 9.5mm)

### Playback Media Formats Video

MPEG-1 (AVI, MPG, DAT)

MPEG-2 (AVI, VOB)

MPEG-4 (AVI, DivX, XviD)

**Audio:** MP3

**Photo:** JPG baseline and progressive up to 8 mega pixel, Motion JPEG (15, 30fps)

**Supported File system:** FAT32 (single or up to 4 multiple partitions)

**Operating System:** ESS technology

**Bus Interface:** USB 2.0 High Speed (USB1.1 backwards compatible)

### Output Interfaces:

**Video:** NTSC/PAL Composite Video, S-Video (720p)

**Audio:** Dual Stereo Analog Audio

### System Requirements:

Windows 98SE, Win2000, WinME, WinXP

Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card

### Power Supply:

External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.6A, 50-60Hz Output: DC +5V/2A Bus Power

**Enclosure Size:** 13.2cm x 7.8cm x 1.8cm

### Packing Contents:

Mvisto Light (no HDD included)

USB 2.0 cable, AV cable

Infrared Remote Control

Power Adapter

Manual, screw package, driver CD



## Mvisto (USD103.1)



### Specifications

'Mvisto' is much more than a portable disk. It allows you to enjoy your favorite movies, music and photos while on the road. It produces HDTV quality Video and Dolby Digital or DTS quality Audio for your pleasure. With lightning-fast USB 2.0, the 'Mvisto' offers hot plug and play, super-speedy data transfer and remarkable versatility. Instant backup! Instant storage! Instant Fun! No more expensive pay per view movies in a lonely hotel.

**Model No. :** MV-U2UGS

**Color:** Silver (other colors available on request)

**Case Material:** Brushed Aluminum

**Application:** Any 2.5" Parallel ATA Hard Drive (Notebook size HDD up to 9.5mm)

#### Playback Media Formats Video:

MPEG-1 (AVI, MPG)

MPEG-2 (AVI, VOB), ISO

MPEG-4 (AVI, DivX, DivX VOD, XviD)

#### DivX Subtitle

SUB (*Micro DVD format*), SRT (*Sub RIP format*), SMI (*SAMI format*), Embedded Multiple Subtitle support

**Audio:** WAV, MP3, MPEG-4 (AAC), WMA, AC3, OGG Vorbis

**Photo:** JPG baseline and progressive up to 8 mega pixel (RGB)

**Supported File system:** NTFS, FAT32, HFS+

**Operating System:** Embedded Linux (v2.4 ucLinux)

**Bus Interface:** USB 2.0 High Speed (USB1.1 backwards compatible)

#### Output Interfaces:

**Video:** NTSC/PAL Composite Video, S-Video, Analog YPbPr Video, SCART RGB, VGA (1024x768),  
HDTV (480p, 720p, scalable up to 1080i)

**Audio:** Dual Stereo Analog Audio supporting compressed Dolby Digital 5.1 and DTS pass through

#### System Requirements:

Windows 98SE, Win2000, WinME, WinXP

Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card

#### Power Supply:

External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 0.4A, 50-60Hz    Output: DC +5V/2A    USB Bus Power

**Enclosure Size:** 13.2cm x 8.0cm x 1.7cm

#### Packing Contents:

Mvisto (no HDD included)



USB 2.0 cable, AV cable, SPDIF Coaxial Cable

Infrared Remote Control

Power Adapter

Manual, screw package, driver CD

## Remarks:

\*ISO = One image file backup of the complete DVD. 'Mvisto' will play the ISO file exactly the same as if it was running from the original DVD!

\*\* Official DivX Certified™ product. Plays DivX® 5, DivX® 4, DivX® 3 and DivX® VOD video content (in compliance with DivX Certified™ technical requirements)

\*\*\* AAC stands for "[Adaptive Audio Coding](#)" and does not support AAC files created by iTunes!

# Does not support High Definition content (DivX HD/WMV9)

## TVisto (USD130)



## Specifications

The 'TVisto' Multimedia Center offers extra capacity for large files, allowing you to store plenty of data, music, photos and even complete movie collections. It produces high quality video and Dolby Digital 5.1 surround audio for your pleasure. With lightning-fast USB 2.0 or Firewire 400, the 'TVisto' offers hot plug and play, super-speedy data transfer and remarkable versatility. Instant backup! Instant storage! Instant Fun!

**Model No. :** TV-FRU2UPS

**Color:** Silver and Black

**Case Material:** Brushed aluminum panels with plastic body

**Application:** Any 3.5" Parallel ATA Hard Drive (Desktop size HDD)

### Playback Media Formats Video

MPEG-1 (AVI, MPG)

MPEG-2 (AVI, VOB), ISO

MPEG-4 (AVI, DivX, DivX VOD, XviD)

### DivX Subtitle

SUB (*Micro DVD format*), SRT (*Sub RIP format*), SMI (*SAMI format*), Embedded Multiple Subtitle support



**Audio:** WAV, MP3, MPEG-4 (AAC), WMA, AC3, OGG Vorbis

**Photo:** JPG baseline and progressive up to 8 mega pixel

**Supported File system:** NTFS, FAT32, HFS+

**Operating System:** Embedded Linux (v2.4 ucLinux)

**Bus Interface:** USB 2.0 High Speed (USB1.1 backwards compatible), Firewire 400 (IEEE 1394a)

**Output Interfaces:**

**Video:** NTSC/PAL Composite Video, S-Video, Analog YPbPr Video, SCART RGB, VGA (1024x768),  
HDTV (480p, 720p, 1080i)

**Audio:** Dual Stereo Analog Audio supporting compressed Dolby Digital 5.1 and DTS pass through

**System Requirements:**

Windows 98SE, Win2000, WinME, WinXP

Mac OS 9.2 or higher

Your hardware device must have proper port or PCI card

**Power Supply:**

External Power Adapter universal auto-switching (UL, cUL)

Input: AC 100-240V, 1.2A, 50-60Hz    Output: DC +5V/2A, +12V/2A

**Enclosure Size:** 22.2cm x 15.2cm x 4.8cm

**Packing Contents:**

TVisto (no HDD included)

USB 2.0 cable, AV cable, SPDIF Coaxial Cable

Infrared Remote Control

Power Adapter

Manual, screw package, driver CD

**Remarks**

\* ISO = One image file backup of the complete DVD. 'Mvisto' will play the [".ISO"](#) file exactly the same as if it was running from the original DVD!

\*\* [Additional accessories](#) available on request (MOQ 500pcs)

\*\*\* Plays DivX® 5, DivX® 4, DivX® 3 and DivX® VOD video content (in compliance with DivX Certified™ technical requirements)

\*\*\*\* AAC stands for "[Adaptive Audio Coding](#)" and does not support AAC files created by iTunes!

# Does not support High Definition content (DivX HD/WMV9)