






TFT LCD MONITOR

| MODEL NO. | Pictures | SPECIFICATIONS | U/P(FOB SZ) |
|------------------|----------|--|-------------|
| CT-MEYE -18C | | <ol style="list-style-type: none"> 1.Power Input: 3.0-10V DC 2.AC adapter: Output 5vdc 1A and Input 100-240VAC 3.Battery Box (Used the Ni-Mh battries or AA batteries) 4*12V/1200mAH 4.Power consumption: less than 1.0W 5.Signal Input: PAL/NTSC video signal 6.Pixels: 800*255 7.Sound Function: double-channel stereo 8.Angle of View: 24 degrees digaonal 9.Display size: 36 inches, 2m away 10.Input Terminal:4-pole mini-jack, Ø3.5mm 11.Video: 1Vpp/72Ω 12.Audio: 200m Vrms/20KΩ 13.Power Inupt Terminal: Ø4.0 14.Operation: -10℃-60℃ 15.Storage: -20℃-80℃ 16.Weight: 180g | USD75 |
| CT-MEYE -230C | | <ol style="list-style-type: none"> 1.Power input:DC3.6V-5V 2.Bettyery:AAA battery 3.Power consumption:less than 1W 4.Signal input:NTSC/PAL video signal,remarking in order 5.Sound Function:double-channel stereo 6.Adjustment Function:Variable volume 7.Display size:40inches,2m away 8.Pixels:320H*240V*RGB(230k) 9.View angle:27degrees 10.Operation temperatures:-20℃~+60℃ 11.For the purpose of improvements 12.design and specifications are subject to change without notice. 13.Accessories:AC adaptor,output 5vdc 1A,input 100VAC-240VAC,cables,battery box | USD98 |

| | | | |
|--------------------------|---|---|-----------------|
| <p>CT-MEYE -922C</p> |  | <ol style="list-style-type: none"> 1.Power input:DC9V 2.Bettery:AAA battery 3.Power consumption:less than 1.5W 4.Signal input:NTSC/PAL video signal,remarking in order 5.Sound Function:double-channel stereo 6.Adjustment Function:Variable volume,brightness,contrastness 7.Display size:45inches,2m away 8.Pixels:640H*480V*RGB(922k) 9.View angle:28degrees 10.Operation temperatures:-20°C~+60°C 11.For the purpose of improvements 12.design and specifications are subject to change without notice. 13.Accessories:AC adaptor,output 9vdc 1A,input 100VAC-240VAC,cables,battery box,PC adapting cable,wireless devices | <p>USD193</p> |
| <p>CT-M70W3</p> |  | <ol style="list-style-type: none"> 1.Screen:7" TFT LCD 2.System: PAL/NTSC 3.Pixels: 1440x234 4.Audio Output:150mW 5.Speaker:32mm round type 6.Black Light: High Luminance Fluorescent Light Tube 7.Power Supply:DC12V 8.Dimension:191mm(L)x 132mm(H)x24mm(W) 9.Terminals: AV Input 10.OSD Language: English | <p>USD52.00</p> |
| <p>CT-M820</p> |  | <ol style="list-style-type: none"> 1.Screen size:8inches 2.Terminals: Video Input, Audio L/R Input,S-Video Input,VGA input 3.Power Supply: DC10-15V 4.System:PAL, NTSC 5.Pixel:921,600 6.VGA:640x480@60Hz 7.Luminance:250cd/m² 8.Audio Amplifier:0.5wx2 9.OSD:English | <p>USD84.00</p> |

- 1.Payment:50% TT of deposit,or 100% irrevocable L/C at sight,balance against shipment.
- 2.MOQ:500units.